



Loyalty-Secu Electronics Co., LTD

www.loyalty-secu.com

Add: 5th Floor,1A Building, Yunantong Industrial Park
Longhua District,Shenzhen,518109, China.

Tel: 86-755-8837 0149

1080P 25X High Speed IP PTZ Camera

LY-IPP-6T07-25

Main Features:

- **HD-IP 2MP ,Camera Solution:**
Hi3516D+Sony327, H.265
- **25X Optical zoom+4X Digital Zoom,**
Lens: 4.7- 117mm
- **6 Inch All Metal Housing, High Speed Dome**
- **Waterproof/Dustproof: IP66**
- **6 PCS Array IR LEDs + 4 PCS Laser LEDs,**
Work Distance up to 300M
- **Starlight, Ultra low Illumination**
- **PTZ Camera Speed: 240°/S**
- **Free APP: Danale**
- **POE+AC24C+DC12V+Audio+Alarm Function**
for Optional
- **Auto Tracking & Intelligent Analysis**



Highlights

- Full metal housing,6 inch high speed PTZ camera
- Camera solution: Hi3516D+Sony327 ,25X Optical zoom+4X Digital zoom, Lens: 4.7- 117mm
- 6 PCS Array IR LEDs + 4 PCS Laser LEDs ,Work Distance Up to 300M
- Auto-Tracking & Intelligent Analysis
- Starlight, Ultra low Illumination
- High Speed PTZ : Horizontal 0.1- 240°/S, Vertical 0.1- 180°/S, 360°continuous rotation
- ONVIF protocol ,Support most of the NVR, such as Hikvision,Dahua,XM,etc
- Support Private protocol with Hikvision NVR, CMS
- Support P2P, ,XMEYE CLOUD ,mobile remote&3D positioning
- Support POE +Audio input+ DC output for Mic
- Preset cruise, pattern scanning, area scanning, 360°horizontal scanning
- Housing: All metal material
- Waterproof: IP66, Lighting protection: 6000V
- Power Supply: DC12V-4A
- Optional Functions:
 POE+ Audio+Alarm+CVBS+AC24V+DC12V
 RS485+Audio+Alarm+CVBS+DC12V
 RS485+Audio+Alarm+CVBS+AC24V

Auto-Tracking PTZ Camera Datasheet:

Camera	
Model	LY-IPP-6T07-25
Image Sensor	Sony CMOS IMX327
DSP	Hi3516D
Minimum Illumination	Color: 0.01Lux, 0 Lux with IR Starlight ultra low illumination
3D NDR	Support
WDR	Support

Electronic Shutter	Supports automatic and manual electronic shutter 1/3~1/30000s
Day Night Mode	AUTO ICR Color to B/W
Penetrating fog	Electronic penetrating fog: Auto and manual
Anti-shake	digital anti-shake
Focal Length	4.7- 117mm,25X Optical Zoom
Digital Zoom	4X
Zoom Speed	Approx.3.5s(Optical Wide~Tele)
Angle of View:	58-2.8 degree(Wide-Tele)
Resolution	1920(H)x1080(V)
Main Stream	30fps/25fps@1080P(1920×108)
Sub Stream	30fps/25fps@(704×576),(640×480),(648×360)
Video Compression	H.265/H.264/MJPEG
Network protocol	HTTP ,FTP,SMTP,UPnP,SNMP, DDNS,NTP,RTSP,RTP,TCP,DHCP, PPPoE
Interface protocol	ONVIF 2.4
PTZ Control	
Work Distance	Up to 300m
Horizontal Range	0°~360° continuously
Vertical Range	-10°~90°
Horizontal Speed	0.05°~240°/s
Vertical Speed	0.05°~180°/s
Max Speed	240°/s
Preset	256
Patrol	4pcs(10 preset for each)
L/R Scan	1pc
Horizontal Scan	1pc
Power-off memory	Support
AI Function	Auto tracking + Intelligent Analysis
Park Action	Watch position/ Area Scan /Horizontal 360°scan/ Cruise/Auto-Tracking
Watch position	Support

Wide angle speed limit	Focus / speed automatic matching function
General	
POE supply voltage	DC48V
POE supply PIN	1,2(+),3,6(-) / 4,5(+),7,8(-) Auto adaptation
Power	DC12V/4A
Consumption	<22W
Mounting	Wall mounting or lifting
Work Environment	Temperature : -20~60°C; Humidity<90%
Protection level	IP66 waterproof, 6000V lightning protection
GW	4.5KG
Power	DC12V/4A
Consumption	<22W
Mounting	Wall mounting or lifting
Dimension	300.5*ø216mm

Product Dimension:

