



Loyalty-Secu Electronics Co., LTD

www.loyalty-secu.com

Add: 5th Floor,1A Building, Yunantong Industrial Park
Longhua District,Shenzhen,518109, China.

Tel: 86-755-88370149

6 Inch 2MP POE 33X HD IP PTZ Camera

LY-IPP-6T07-33

Main Features:

- **Full HD-IP 2MP/1080P ,Camera Solution:**
Hi3516Ev200+GC2053
- **Lens: 33X Optical zoom, 4.5- 148mm**
- **6 Inch All Metal Housing, High Speed Dome**
- **Waterproof/Dustproof: IP66**
- **6 PCS Array IR LEDs + 4 PCS Laser LEDs,**
Work Distance up to 300M
- **PTZ Camera Speed: 240°/S**
- **Two Way Audio**
- **Auto-Tracking, Humanoid Detection**
- **Built-in PoE (IEEE802.3at),48W POE Injector**
- **Cost Effective 33X 2MP Solution**

Free APP: SmartViewer Pro



Highlights

- 6 PCS OSRAM IR Array LEDs+ 4 PCS Laser LEDs, IR Distance up to 300M
- Camera Solution: **Hi3516Ev200+GC2053**,2MP/1080P High definition
- 33X optical zoom, Lens: 4.5~148mm
- High Speed PTZ : Horizontal 0.1- 240°/S, Vertical 0.1- 180°/S, 360°continuous rotation
- ONVIF protocol ,Hikvision private protocol,i9, S-link protocol
- Support P2P, PC/iOS/Android remote control
- Preset cruise, pattern scanning, area scanning, 360°horizontal scanning
- Housing: all metal material, Waterproof: IP66, Lighting protection: 6000V
- Built-in PoE (IEEE802.3at),with 65W POE injector, brings super long 250m POE work distance
- Intelligent AI functions(Humanoid Detection and Alert Auto Tracking), Sound and light alarm function, two way audio
- Support guard tracking, cruise tracking, auto zoom and track
- Full metal housing, Waterproof:IP66, Lighting protection: 6000V
- **Accept other 2MP Camera Solution Customization**

33X POE IP PTZ Camera Datasheet:

Camera	
Model	LY-IPP-6T07-33
DSP	Hi3516Ev200
Minimum Illumination	Color: 0.01Lux, 0 Lux with IR Starlight ultra low illumination
3D NDR	Support
WDR	Support
Electronic Shutter	Supports automatic and manual electronic shutter 1/3~1/30000s
Day Night Mode	AUTO ICR Color to B/W
Penetrating fog	Electronic penetrating fog: Auto and manual
Anti-shake	digital anti-shake

Focal Length	4.5- 148mm,33X Optical Zoom
Zoom Speed	Approx.3.5s(Optical Wide~Tele)
Angle of View:	58-2.8 degree(Wide-Tele)
Resolution	1920(H)x1080(V)
Main Stream	30fps/25fps@1080P(1920×108)
Sub Stream	30fps/25fps@(704×576),(640×480),(648×360)
Video Compression	H.265/H.264/MJPEG
Network protocol	HTTP ,FTP,SMTP,UPnP,SNMP, DDNS,NTP,RTSP,RTP,TCP,DHCP, PPPoE
Interface protocol	ONVIF 2.4
PTZ Control	
Work Distance	Up to 300m
Horizontal Range	0°~360° continuously
Vertical Range	-10°~90°
Horizontal Speed	0.05°~240°/s
Vertical Speed	0.05°~180°/s
Max Speed	240°/s
Preset	256
Patrol	4pcs(10 preset for each)
L/R Scan	1pc
Horizontal Scan	1pc
Power-off memory	Support
Park Action	Watch position/ Area Scan /Horizontal 360°scan/ Cruise
Watch position	Support
AI Functions	Humanoid Detection & Alert Auto Tracking
Wide angle speed limit	Focus / speed automatic matching function
General	
POE supply voltage	DC48V
POE supply PIN	1,2(+),3,6(-) / 4,5(+),7,8(-) Auto adaptation
Power	DC12V/4A

POE Injector	48W 120m work distance
Consumption	<22W
Work Environment	Temperature : -20~60°C; Humidity<90%
Protection level	IP66 waterproof, 6000V lightning protection
GW	4.5KG
Mounting	Wall mounting or lifting
Dimension	300.5*ø216mm
Free App	SmartViewer Pro

Product Dimension:

