



**Loyalty-Secu Electronics Co., LTD**

[www.loyalty-secu.com](http://www.loyalty-secu.com)

Add: 5th Floor,1A Building, Yunantong Industrial Park  
Longhua District,Shenzhen,518109, China.

Tel: 86-755-8837 0149

## **5MP 33X Zoom Infrared PTZ Dome IP Camera**

**LY-UPP-E6T35**

### **Main Features:**

- **Full HD-IP 5MP**
- **Lens: 33X Optical zoom, 4.5-148.5mm**
- **6pcs OSRAM IR Array LEDs + 4pcs Laser LEDs, IR Distance up to 250M(820ft)**
- **Free APP: EZView**
- **120db Optical Wide Dynamic Range**
- **AI Function: Face Detection & Auto Tracking, Multi-Behaviors Detection**
- **With POE & POE Injector, Full Metal Housing**
- **Built-in Microphone and Speaker, Two Way Audio**
- **PTZ Camera Speed: 0.05-240°/S**
- **ONVIF protocol ,Uniview private protocol**

## Product Description

### 6 Inch 5MP 33X IP PTZ Camera Features:

- 6pcs OSRAM IR Array LEDs + 4pcs Laser LEDs, Laser IR Distance up to 150M
- 5MP (1920P) security PTZ cameras are super high definition cameras that record class-leading **5-megapixel** images with enhanced camera sensors, high resolution of 2560\*1920.
- Built-in microphone and speaker, two way audio
- High Speed PTZ 0.05-240°/S, 360°all-frame endless rotation
- Behaviors detection: cross border detection, regional invasion, entering area, leaving area, wandering detection, rapid movement, personnel gathering, parking detection, items left behind, objects movement
- Face detection , passenger flow statistics, auto-tracking
- ONVIF protocol ,Uniview private protocol
- SUPPORT P2P, PC/iOS/Android remote control
- Built-in POE++ (48W)
- 6 Inch full metal housing
- Weather-proof,waterproof:IP66, lighting protection: 6000V
- With standard 65W Super POE injector, POE transmission distance up to 200M
- Using the high accuracy stepping motor, work with the high performance motor driver, ensure the PTZ camera work under a stable, accurate, and less vibration condition
- Support watch position, power on action, idle action,4 pcs cruise scan, track scan, two point scan,360 degree scan

**33X Zoom IP 5MP PTZ Security Camera Datasheet:**

<b>Camera</b>	
Model	LY-UPP-E6T35
Camera Solution	<b>Uniview Solution</b>
Minimum Illumination	Color: 0.001Lux, B/W: 0.001Lux, 0 Lux with IR <b>(Starlight Ultra low illumination)</b>
3D NDR/WDR	Support
Electronic Shutter	AUTO
Day Night Mode	AUTO ICR Color to B/W
Focal Length:	4.5-148.5mm, 33X Optical Zoom
Zoom Speed	Approx. 4s (Optical Wide~Tele)
Angle of View:	55.4-2.9° (Wide-Tele)
Resolution	2592(H)x1944(V)
Main Stream	2592 x 1944, 2592 x 1520, 1920 x 1080
Sub Stream	D1, VGA, 640x360
Video Compression	H.265+/H.265/H.264
Network protocol	HTTP/RTSP/RTMP/DHCP/NTP/ONVIF/NTP/UPNP/GB28181
Interface protocol	ONVIF 2.4, Uniview private protocol
AI function	<b>Face Detection &amp; Auto Tracking, Multi-Behaviors Detection</b>
APP	EZView
<b>PTZ Control</b>	
IR Distance	250m(820ft)
Horizontal Range	0°~360° continuously
Vertical Range	-5°~90°
Vertical/Horizontal Speed	<b>0.05°~240°/s</b>
Max Speed	240°/S
Preset	256
Patrol scan	4pcs(10 preset for each)
L/R Scan	1pc
Horizontal Scan	1pc

Power-off memory	Support
PARK Action	Watch position/ Area Scan /Horizontal 360°scan/ Cruise
Watch position	Support
Wide angle speed limit	Focus / speed automatic matching function
<b>General</b>	
POE supply voltage	DC48V
POE Supply Pin	1,2(+) 3,6(-) / 4,5(+) 7,8(-) Auto adapting (IEEE802.3at)
Power/Consumption	DC12V/4A,<22W
Mounting	Wall mounting or lifting
Work environment	Temperature : -20~60°C; Humidity<90%
Protection level	IP66 waterproof,6000V lightning protection
GW(KG)	4.5KG

**Product Dimension:**

