6 Inch 2MP 22X 60W/40AH Solar Powered 4G LTE IP PTZ Camera Kit

:	1. Sellii	ng Points
:		f Introduction
;	3. PTZ	Camera's Features
!	5. Othe	er Features
	5.1.	No Troubles With Network Connection and Power Supply Any More!
	5.2.	Get Notified with Smartphone & Dual Audio Solution
	5.3.	Excellent Video Quality Even at Night6
	5.4.	Smart Automatically Patrol6
	5.5.	Waterproof IP66 & 4000V Thunder-proof
	5.6.	Support Local Storage and Playback
	5.7.	Intelligent WDR Function& Real Color
(6. Wha	at's Included?
8	8. PTZ	Camera Specification
9	9. Solai	Camera Specification
:	10. Pr	roduct Dimension13
		Section
		(0)
		Y
	Ó	
	10	
<	17	
Shen		
5		
		ununu lavaltu saau sam

LOYALTY-SECU 60W/40AH Solar Powered 4G LTE Wireless Outdoor

1080P Pan Tilt WiFi Security Camera with Two-Way Audio, IP66

Weatherproof, Night Vision 200M (656ft) and Built-in SD Slot

LY-U6-222WG-60W

1.Selling Points

- i. **2MP 3G 4G/LTE WiFi Solution**: 4G 2MP PTZ camera allows users to setup surveillance devices in locations without WiFi coverage through 4G/LTE data plan (micro 4G sim card is not included), meanwhile, it supports to setup PTZ camera in locations via WiFi network, when there has poor 4G signals coverage.
- ii. **Outdoor Monitoring & Two-way Audio:** Outfitted with industrial-level IP66 waterproof shell to tackle extreme weathers and two-way audio function allows people to talk to the person at the camera's end through APP Guard Viewer.
- iii. **Easy Installation 60W Solar Panel & 40AH Solar Battery Powered:** It is completely equipped with accessories which are suitable for a variety of installation scenes. A rechargeable 40AH solar battery powered with 60W solar panel gives you a reliable and powerful wireless security camera system in your domain.
- iv. **Capture More Details with 22X Optical Zoom:** The 22X optical zoom lens will leverage the zoom status of the camera according to the distance of a moving object, day and night. The camera is equipped with 1/2.8" Sony CMOS Sensor and delivers 1080p@60fps in H.265.
- v. **Remote Live View & Playback**: Use APP Guard Viewer to remotely view live streams. The security PTZ camera also supports TF card extension up to 256GB (Micro SD card is not included) where users can select to put on for device-end video storage.

2. Brief Introduction



6 Inch 60W/40AH Solar Powered 1080P 22X 4G cellular Security Network PTZ Cameras

LOYALTY-SECU 6inch 2MP LTE Network PTZ Camera utilizes 4G-LTE connectivity. It is ideal to install it where there is no WiFi signal. Meanwhile, it adopts the high accuracy stepping motor, works with the high performance motor driver, which ensures the PTZ IP camera works under a stable, accurate, and less vibration condition.

Also, the LOYALTY-SECU Security PTZ IP camera 1080P comes alone with a 60W solar powered kit which is suitable for places where there are no any power supply facilities.

3.PTZ Camera's Features

- i. H.265/H.264 video compression, 1920*1080P, 22X optical zoom, 5.4- 114.4mm lens
- ii. High speed pan tilt zoom with Horizontal: 0-360 Degree, Vertical: 0-90 Degree
- iii. 6pcs IR Array LEDs+4pcs Laser LEDs, support starlight function, night vision up to 200M (656ft)
- iv. Support any brand NVR with ONVIF protocol
- v. P2P mode with Plug & play, one tap QR code scanning to view live streaming of PTZ camera on iPhone and android phone via APP Guard Viewer
- vi. Two-way audio with built-in mic & speaker allows users to speak with anyone on the camera's end through smartphone app with warning decal for compliance purpose.
- vii. Industrial-level IP66 waterproof shell with an operating temperature rating at $-20\sim60^{\circ}$ C to tackle extreme weathers.
- viii. Support different network mode connection: Auto mode/3G-4G mode/WiFi mode

4. Solar Power System's Features

- ix. Equipped with the high quality 18V/60W monocrystalline silicon solar panel and 12V/40AH EV MnNiCo ternary 18650 Lithium battery.
- x. With the real-time monitoring for the solar panel work condition, lithium battery's work condition and the transformation of load power consumption.
- xi. With the frequency conversion lithium battery charging technology, accomplish the high effective charging process and high-accuracy lithium battery charging curve, Max charging efficiency can reach to 99%.
- xii. With the built-in Ultra low power lithium battery protection function, includes: Over Charge, Over Discharge, Overcurrent, Short- circuit Protection, Temperature Detection etc.
- xiii. Upgraded solar power kit with built-in battery charge and discharge protection control board and intelligent solar controller, ensure the whole solar power supply process is safe and high efficiency.
- xiv. Adopt Hikvision similar bracket installation design, truly "plug and play" function, high waterproof performance IP67.

5. Other Features

5.1. No Troubles With Network Connection and Power Supply Any More!

LOYALTY-SECU Solar Powered WiFi 4G LTE PTZ Camera Kits are widely used in outdoor sites which are not equipped with power supply facilities, such as the mountain orchard, ranch, fishery, vegetable plantation, construction sites, highway roads, farm and animal husbandry, reservoir and so on.

Meanwhile, it is ideal to install it where there is no WiFi coverage. Just need to insert a 4G sim card in the security camera, and download an APP on the mobile, then you can monitor anytime, anywhere.



5.2. Get Notified with Smartphone & Dual Audio Solution

Remotely watch live view & playback and control PTZ/Preset through APP Guard Viewer (iOS & Android) with alarm message pushed. Alarm pictures will be sent by Email; meanwhile, pictures and videos can be uploaded to the FTP server

PTZ IP camera comes with built-in mic & speaker allows users to speak with anyone on the camera's end through smartphone app with warning decal for compliance purpose.



5.3. Excellent Video Quality Even at Night

The 4G PTZ Camera with 6 pcs high quality array LEDs +4 pcs laser LEDs which brings an excellent IR night vision at 200m. The infrared illumination distance can reach up to 200m depending on the scene. **Meanwhile, it supports starlight function.**



5.4. Smart Automatically Patrol

Support preset cruise points, time and speed-patrol in the monitoring zone you cared!

Patrol: Up to 4 patrol groups;

Preset: 10 presets per patrol group

Patrol time: Adjustable

Our PTZ Security Camera supports "Cruise" and "Auto Tracking" simultaneously! Secure your cares through both Cruise and Auto Tracking

- i. When there is no human movement detected, the PTZ security camera will cruise according to your preset trajectory.
- ii. When there is human detection, this network security camera will auto tracking the human until the human disappears in the field of view. Then it will resume cruise.



5.5. Waterproof IP66 & 4000V Thunder-proof

The security outdoor camera is equipped with an IP66 rated weatherproof metal shell and supports **4000V Thunder-proof**, designed to operate the security PTZ camera even in some real extreme weather conditions.



5.6. Support Local Storage and Playback

The network PTZ camera supports micro TF card up to 256GB. Insert a TF card, and then it is a complete remote video surveillance system. When the TF card is full, the new recordings will overwrite the old ones, it can make sure the recording of security camera works normally all the

time. Meanwhile, you can view the live streams of PTZ camera and play videos via your mobile phone APP remotely.



5.7. Intelligent WDR Function& Real Color

With true WDR technology, it can produce images of good clarity even under varying light conditions by using different shutter speeds to allow more light in some darker areas of the image and less light in others brighter. The sensor's exposure to light-receiving from the exterior environment is controlled to achieve a compensated vision.



6. What's Included?

For PTZ camera:

1pcs Manual, 1pcs PTZ Camera, 1pcs Wall Bracket (default), 1pcs 12V/4A adapter and 1set install screws

For Solar Power Kit:

1pcs Solar Panel, 1pcs Lithium Battery, 1 Set Bracket, 1 Set Install Screws.

60W/40AH Solar Power PTZ Camera Kit





7.

8.PTZ Camera Specification

Model	LY-U6-222WG
Sensor	1/2.8" Sony CMOS
Resolution	1080P (1920*1080) up to 60fps
Pixel	2MP
WDR	120dB
APP	Guard Viewer
Al Features	Auto Tracking/Face Detection/Humanoid Detection
Behavior	Cross-border detection, regional intrusion, entering the area, leaving the area,
Detection	wandering detection, fast moving, people gathering, parking detection, item
	leftover, item moving
Lens	22X Zoom (5.4- 114.4mm)
Aperture	Auto/manual, aperture range: F1.5~F3.8
Minimum	Color: 0.005Lux, B/W: 0.0005Lux, 0Lux with IR

Illumination	
Day/Night	Support IR-cut
Mode	
IR Distance	200M
Motion	A congrete test areas can be set (Sonsitivity can be set)
Detection	4 separate test areas can be set (Sensitivity can be set)
Alarm Linkage	Send pictures by Email; pictures and videos uploaded to the FTP server;
Manual Speed	0.5-100°/S
Preset Speed	100°/S
OSD	OSD name, time, date, information overlay
Video Stream	Three-stream encoding capability to meet real-time streaming and storage
	streaming requirements of different bandwidths and frame rates
	General
Network	L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP,DNS,DDNS,NTP,FTP,UPnP,
Interface	HTTP,SNMP,SIP
	North America:
	LTE FDD: B2/B4/B5/B12/13/B14/B66/B71;
	WCDMA: B2/B4/B5
Band	Europe:
Information	LTE FDD: B1/B3/B7/B8/B20/B28A; LTE TDD: B38/B40/B41; WCDMA: B1/B8
	Japan:
	LTE FDD: B1/B3/B8/B18/B19/B26; LTE TDD: B41; WCDMA: B1/B6/B8/B19
	Can be customized according to the region
Presets	256
Audio Interface	1 input / 1 output
Cruise/ A-B Scan	4 groups/1
Preset Number	10 preset/ groups
of Cruise Groups	
SSID	SSID can be set to hide or open, SSID name password can be modified
Breakage	Support, when the device fails to go offline on the public network, it is detected
self-test repair	every 2 minutes and the connection is automatically reconnected.
IP Address	Support static IP and dynamic IP (DHCP)
Motion	Support
detection	
Email alert	Support
FTP upload	Support
Waterproof	IP66
Grade	

Lightning	4000V
Protection	
Working	(-20°C∼+60°C)
Temperature	
Power Supply	12V 4A
GW	3.9KG

9. Solar Power System Specification

Solar Power Kit (60W Solar Panel + 40AH Solar Battery)			
Solar Power Kit Model	LY-SPS-6040AH		
Solar Power Kit Include Items	1PCS Solar Panel, 1 PCS Lithium Battery, 1 Set Bracket, 1 Set Install Screws		
Solar Power Kit Carton Size	73*65*22CM		
Solar Power Kit GW	17KG		

60W Solar Panel	
Solar panel type	Monocrystalline silicon 60W
Solar panel	18V/60W
Voltage/Consumption Power tolerance	+3%
Rated voltage	17.56V
Service life	25 Years
Maximum power	60W
Maximum power voltage	17.56V
Maximum current	2.85A
Short-circuit current	3.45A
Open-circuit Voltage	22.32V
Temperature coefficient of ISC	+0.04
TC of VOC	-0.38
TC of Consumption	-0.47
TC of IM	+0.04

TC of VM	-0.38
Temperature range	-40° ~ +85°
Rated current of bypass	12A
diode	
Load capacity	23m/s,7.53g
Max load capacity of Surface	2400Pa
Solar panel size	59*67*3CM
Solar panel weight	5.25KG

40AH Lithium Battery	
Battery cell	EV MnNiCo ternary 18650 Lithium
Battery capacity	Min 40Ah,Max 40.9Ah
Nominal voltage	12V
Charge/Discharge protection	12.6V/9V
voltage	
Normal charging current	10A
Max Charge/Discharge	20A
current	
Discharge temperature	-20°~ 60°
(Recommend)	69
Charge temperature	-5°~45°
(Recommend)	
	1.Solar panel with an-reverse protection
	2.Support the tracking for the Max power generation efficiency
10,	of solar panel
Intelligent Solar power	3.Support the real-time detection of generation voltage and
system	generation current, and the data upload
	4.Support the detection of battery capacity, and the data upload
	5.Support the detection of total load's real-time current ,and the
Y	data upload
	6. With the low voltage protection technology
Storage time	≥18 months(25°)
Battery weight	4.5KG

10. Product Dimension

